


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 0.8–3.5 GHz
 Insertion Loss: 0.6dB Max.
 Isolation: 18dB Min.
 VSWR: 1.40:1 Max.
 Amplitude Balance: ±0.5dB Max.
 Phase Balance: ±8 Deg. Max.
 Power: 30W (Load vswr@1.2)

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-8254 FAX: (727) 381-6116 http://www.MCLI.COM		SCALE:	N/A	
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE:		2-WAY POWER DIVIDER	
DRAWN:		Paiboon Luekhamhan	DATE:	04-23-1999	PART NO.		PS2-80
APPROVED:		T. Nguyen	DATE:	04-23-1999	CAGE CODE:	SIZE:	REV:
					OD2L5	A	N/A
					DO NOT SCALE THE DRAWING		DWG NO.
							81304