


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 10–15 GHz
 Isolation: 18dB Min.
 VSWR: 1.50:1 Max.
 Insertion Loss: 0.6dB Max.
 Amplitude Balance: ±0.3dB Max.
 Phase Balance: ±8 Deg. Max.
 Power: 30 Watts

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.004 ANGLE: ±1/2°	DRAWING TITLE:		SHEET:
			2-WAY POWER DIVIDER			
			PART NO.		PS2-90	
DRAWN:	DATE:	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	CAGE CODE:	SIZE:	REV:	DWG NO.
APPROVED:	DATE:		OD2L5	N/A	N/A	81282
		THIRD ANGLE PROJECTION	DO NOT SCALE THE DRAWING			