


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 1.2–1.4 GHz
 Insertion Loss: 0.5dB Max.
 Isolation: 22dB Min.
 Phase Balance: ± 6 Deg. Max.
 Amplitude Balance: ± 0.2 dB Max.
 VSWR: 1.25:1 Max.
 Power: 20W (Load vswr@1.2)

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$			DRAWING TITLE: 3-WAY POWER DIVIDER		SHEET: N/A
DRAWN: Paiboon Luexhamhan		DATE: 11-18-2001		PART NO. PS3-95	
APPROVED: T. Nguyen		DATE: 11-18-2001		CAGE CODE: OD2L5	SIZE: A REV: N/A DWG NO.: 81920
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		THIRD ANGLE PROJECTION 		DO NOT SCALE THE DRAWING	