


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 11.7–12.2 GHz
 Insertion Loss: 2.1dB Max.
 Isolation: 14dB Min.
 VSWR: 1.70:1 Max.
 Power: 30W CW
 Amplitude Balance: ±0.7dB Max.
 Phase Balance: ±10 Deg. Max.

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.mcli.com	SCALE:	N/A
			SHEET:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: 4-WAY POWER DIVIDER		
DRAWING: Paiboon Luexhamhan		PART NO.: PS4-138/NF		
DATE: 02-25-1998	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	
APPROVED: T. Nguyen	DATE: 02-25-1998	THIRD ANGLE PROJECTION	SIZE: C	REV: N/A
			DO NOT SCALE THE DRAWING	
			DWG NO.: 81212	