


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



**SPECIFICATIONS**

Frequency Range: 4–8 GHz  
 Isolation: 18dB Min.  
 VSWR In/Out: 1.50:1/1.40:1 Max.  
 Insertion Loss: 0.5dB Max.  
 Amplitude Balance: ±0.3dB Max.  
 Phase Balance: ±6 Deg. Max.

MATERIAL:		 <b>MCLI</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://www.mcli.com">http://www.mcli.com</a>	SCALE:	N/A
			SHEET:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°	DRAWING TITLE: <b>4-WAY POWER DIVIDER</b>	
DRAWING: Paiboon Luekthamhan		DATE: 04-10-2007	PART NO.: PS4-6/NF	
APPROVED: T. Nguyen		DATE: 04-10-2007	CAGE CODE: OD2L5	SIZE: N/A
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	REV: N/A	DWG NO.: 82821
		 THIRD ANGLE PROJECTION	DO NOT SCALE THE DRAWING	