



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 0.4–2.7 GHz
 Insertion Loss: 2.3dB Max.
 Isolation: 17dB Min.
 VSWR Input/Output: 1.50:1/1.40:1 Max.
 Amplitude Balance: ±0.3dB Max.
 Phase Balance: ±5 Deg. Max.
 Power: 20W (vswr@1.2)

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			SHEET:	N/A
DRAWN:		DRAWING TITLE:		
DATE:		4-WAY POWER DIVIDER		
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		PART NO.		
DRAWN: Paiboon Luekhamhan DATE: 10-25-1997		PS4-77		
APPROVED: T. Nguyen DATE: 10-25-1997		CAGE CODE:	SIZE:	REV:
		OD2L5	A	N/A
		DO NOT SCALE THE DRAWING		DWG NO.
				81002