



SPECIFICATIONS

Frequency Range: 2–13 GHz
 Insertion Loss: 3.9dB Max.
 Isolation: 16dB Min.
 Amplitude Balance: ±1.9dB Max.
 VSWR IN/OUT: 1.80:1/1.90:1 Max.
 Average Power: 20W (Load vswr@1.2)

MATERIAL:		 MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.mcli.com	SCALE:	N/A
			SHEET:	N/A
		<small>UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± .02 ± .008 ANGLE: ± 1/2°</small>	DRAWING TITLE: 6-WAY POWER DIVIDER	
		<small>PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)</small>	PART NO.: PS6-11/NF	
DRAWN: Paiboon Luekhamhan	DATE: 05-30-2018	<small>THIRD ANGLE PROJECTION</small> 	CAGE CODE:	SIZE: N/A
APPROVED: T. Nguyen	DATE: 05-30-2018		OD2L5	REV: N/A
			DO NOT SCALE THE DRAWING	