



REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED

SPECIFICATIONS

Frequency Range: 0.5–2 GHz
 Insertion Loss: 2.0dB Max.
 Isolation: 16dB Min.
 Phase Balance: ±10 Deg. Max.
 Amplitude Balance: ±0.6dB Max.
 VSWR IN/OUT: 1.70:1/1.60:1 Max.
 Input Power: 20W (Load vswr @ 1.2)

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE: N/A
			SHEET: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.02 ±.008 ANGLE: ±1/2°		DRAWING TITLE: 6-WAY POWER DIVIDER	
DRAWN: Paiboon Luekhamhan DATE: 11-01-1997		PART NO.: PS6-3	
APPROVED: T. Nguyen DATE: 11-01-1997		CAGE CODE: OD2L5	SIZE: N/A REV: N/A DWG NO. 81522
<small>PROPERTY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)</small>		DO NOT SCALE THE DRAWING	