


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 8–40 GHz
 Insertion Loss: 2.4dB Max.
 Isolation: 14dB Min.
 VSWR: 1.80:1 Max.
 Amplitude Balance: ±0.8dB Max.
 Phase Balance: ±9 Deg. Max.
 Power Average: 20W CW, 3kW Peak.

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
			UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET: N/A
DRAWN: Paiboon Luekhamhan		DATE: 07-30-2014		DRAWING TITLE: 6-WAY POWER DIVIDER	
APPROVED: T. Nguyen		DATE: 07-30-2014		PART NO. PS6-39	
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	SIZE: N/A
		THIRD ANGLE PROJECTION 		REV: N/A	DWG NO. 84624
DO NOT SCALE THE DRAWING					