





SPECIFICATIONS

Frequency Range: 1–26 GHz
 Insertion Loss: 4.2dB Max.
 Isolation: 16dB Min.
 CW Power: 20W Max. Peak 3kW
 VSWR: 1.70:1 Max.
 Amplitude Balance: ±1.0dB Max.
 Phase Balance: ±10Deg. Max.

MATERIAL:		 MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.02 ±.009 ANGLE: ±1/2°			DRAWING TITLE:	6-WAY POWER DIVIDER
DRAWN:		Paiboon Luekhamhan	DATE:	01-17-2018
APPROVED:		T. Nguyen	DATE:	01-17-2018
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		PART NO.:	PS6-56-M	
THIRD ANGLE PROJECTION 		CAGE CODE:	SIZE:	N/A
		REV:	N/A	DWG NO.:
		DO NOT SCALE THE DRAWING		86714