



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 0.8–3.0 GHz
 Insertion Loss: 1.8dB Max.
 Isolation: 16dB Min.
 VSWR In/Out: 1.50:1/1.40:1 Max.
 Phase Balance: ±9 Deg. Max.
 Amplitude Balance: ±0.8dB Max.
 Power Rating: 30 Watts

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			DRAWING TITLE:		SHEET:	
DRAWN:		PART NO.		8-WAY POWER DIVIDER		
APPROVED:		CAGE CODE:		PS8-155		
DATE:		SIZE:		REV:		DWG NO.
05-18-2000		N/A		N/A		81532
T. Nguyen		OD2L5		DO NOT SCALE THE DRAWING		
DATE:		THIRD ANGLE PROJECTION				
05-18-2000						