



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 0.8–3.0 GHz
 Insertion Loss: 1.8dB Max.
 Isolation: 16dB Min.
 Power Rating: 30 Watts
 Amplitude Balance: ±0.8dB Max.
 VSWR IN/OUT: 1.50:1/1.40:1 Max.
 Phase Balance: ±9 Deg. Max.

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://www.mcli.com		SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			DRAWING TITLE: 8-WAY POWER DIVIDER		SHEET: N/A
DRAWING: Paiboon Luekhamhan		DATE: 05-18-2000		PART NO.: PS8-155/NF	
APPROVED: T. Nguyen		DATE: 05-18-2000		CAGE CODE: OD2L5	SIZE: C
THIRD ANGLE PROJECTION		REV: N/A		DWG. NO.: 81531	
DO NOT SCALE THE DRAWING					