REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range:	0.96–1.215 GHz
VSWR:	1.35:1 Max.
Insertion Loss:	0.7dB Max.
Isolation:	16dB Min.
Phase Balance:	±6 Deg. Max.
Amplitude Balance:	±0.6dB Max.
Power Rating:	250W (Load vswr@1.2)

MATERIAL:

DRAWN: Paiboon Luekhamhan — DATE: 06-16-1998

APPROVED: T. Nguyen — DATE: 06-16-1998

MCLI

MICROWAVE COMMUNICATIONS LABORATORIES INC.
7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
TEL: (727) 344-6254 FAX: (727) 381-6116
hhtp://WWW.MCLI.COM

SCALE: N/A

SHEET: N/A

UNLESS OTHERWISE SPECIFIED:
TOLERANCES
IN (INCHES) OR [mm] (MILLIMETERS)
FRACTIONS: ± 1/64
DECIMALS: ±.01 ±.005
ANGLE: ±1/2°

PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION

DRAWING TITLE: 8-WAY POWER DIVIDER

PART NO. PS8-35

CAGE CODE: 0D2L5

SIZE: N/A

REV: N/A

DO NOT SCALE THE DRAWING

DWG NO. 81158