


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS


Frequency Range: 1–2 GHz
 Insertion Loss: 0.9dB Max.
 Isolation: 17dB Min.
 VSWR Input/Output: 1.50:1/1.35:1 Max.
 Phase Balance: ±6 Deg. Max.
 Amplitude Balance: ±0.35dB Max.
 Power: 30W (Load vswr@1.2)

MATERIAL:	
	
DRAWN: Paiboon Luekhamhan	DATE: 06-25-1999
APPROVED: T. Nguyen	DATE: 06-25-1999

MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
 http://WWW.MCLI.COM

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR [mm] (MILLIMETERS)
 FRACTIONS: ± 1/64
 DECIMALS: ±0.01 ±0.005
 ANGLE: ±1/2°

THIRD ANGLE PROJECTION



SCALE: N/A	DRAWING TITLE: 8-WAY POWER DIVIDER	
SHEET: N/A	PART NO.: PS8-3/NF	
CAGE CODE: OD2L5	SIZE: N/A	REV: N/A
DO NOT SCALE THE DRAWING		DWG NO.: 80262