



REV		DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

Frequency Range: 1.70–2.60 GHz
 Waveguide Size: WR430 (Input)
 Flange Types: Per Order (-1,-2,-S)
 VSWR: 1.15:1 Max.
 Average Power: 6500 Watts

CPR430F STANDARD
 OTHERS UPON REQUEST

F = FLANGE TYPES

- 1 = CPRG
- 2 = CPRF
- S = SPECIAL

ORDERING INFORMATION

EXAMPLE PART NUMBER: WL-2-F
 VERY HIGH POWER SERIES
 FREQUENCY BAND
 FLANGE TYPE

Aluminum 6061 High Temp. Black Paint	MCLI <small>UNLESS OTHERWISE SPECIFIED:</small> DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED FINISH: 24/10 SURFACE: 60/32 ANGLE: 3/16	ORDER NO.	N/A
		PART NO.	N/A
Pdsoon Luthamhan	05-03-2011	DESCRIPTION	TERMINATION, WR430 6500 Watts
T. Nguyen	05-03-2011	PART NO.	WL-2-F
DRAWN	05-03-2011	PART NO.	85655
CHECKED	05-03-2011	PART NO.	85655
APPROVED	05-03-2011	PART NO.	85655