


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 4–6 GHz
 VSWR: 1.60:1 Max.
 Amplitude Balance: ± 1.0 dB Max.
 Phase Balance: ± 6 Deg. Max.
 Insertion Loss: 2.9 dB Max.
 Isolation: 16 dB Min.
 Input Power: 10W (Load vswr @ 1.2)

MATERIAL: DRAWN: Paiboon Luekhamhan DATE: 03-25-2009 APPROVED: T. Nguyen DATE: 03-25-2009		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A SHEET: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .02 \pm .008$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 16-WAY POWER DIVIDER PART NO.: PS16-41
		CAGE CODE: OD2L5 SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING	DWG NO.: 86731	